

Two Channel 350W Power Amplifier PA-2350P

Description:

The range of public address system or PA system two channel power amplifiers are designed for general commercial and industrial public address applications. Rack mount design in 2U

type, rated power of 2×350W by two channels, which provides a wide selection to meet different size sound system needs. Two unbalanced line inputs could direct input from audio sources or from pre amplifier & mixer. 70V, 100V and 4-16ohm speaker by two channel separate outputs are convenient for installation when selection different speaker matching, also could be taken as two separate zone for individual control. Two channel separate volume controls are included. Complete protection includes clip, short circuit, high temp and overload. Indicators for power, signal, clip, protection and temp.



Feature

- ✓ Rack mount PA 100 Volt two channel power amplifier in 2U type
- ✓ Rated power of 2×350W for dual zone public address system.
- ✓ 70V, 100V and 4-16 ohm two channel separate speaker outputs
- ✓ Isolated transformer for human safety operation
- ✓ Unbalanced two channel line inputs by RCA type.
- ✓ Reliable protection of over heat, over load, clip & short circuit
- ✓ Indications for power, signal, clip, protection and temp
- ✓ DC 24V power supply backup input at request

Specification:

| | |
|---------------------------|---|
| Model | PA-2350P |
| Description | Public Address System Power Amplifier |
| Rated Power Output | 2×350W |
| Speaker Output | 100V, 70V, 4-16Ω |
| Input | unbalanced two RCA line inputs |
| Frequency Response | 60-15KHz |
| S/N Ratio | ≥85dB |
| THD | Less than 0.5% at 1KHz, 1/3 rated power |
| Cooling System | Fan auto open when internal temp reaches 55°C |
| Protection | Temp, overload, short circuit & clip |
| Power Supply | AC230V or 110V, 50-60Hz |
| Power Consumption | 830W |
| Dimensions | 484x366x88mm |
| Weight | 14.5kg |

Rear Panel:

